## BEAK-ROC

WWW.BEAUROC.COM



## DUMP BODIES THAT STAND THE PRESSURE OF TIME

PRODUCT CATALOGUE



CLEAN SIDE

TRADITIONAL

MULTI-PURPOSE

INLESS STEEL

BODY OPTIONS 🗢

### WWW.BEAUROC.COM

Beau-Roc Inc. is the leading premium steel dump body manufacturer and has been building cutting edge designs since 1984. Beau-Roc manufactures a wide variety of dump bodies ranging from our One-Ton Ultra body, to our Extreme Heavy Duty Multi-Purpose/Clean-Up body, and everything in between.

Our Diamond body line, first introduced in 2004, has changed the way that many look at a dump body. Our Diamond Lightweight (DL) is the most versatile body on the market today. Its innovative design uses multifaceted sides without posts. The DL's light weight and extraordinary toughness make it the choice of the industry.

Our mission is to become the reference company to which all others are compared. To achieve this, our goals are leading edge design, quality, and improved partnership with our suppliers, and especially with you our clients.

## GLEANS **BODY LINE**



TOP RAIL	3
SIDES	
SIDE POSTS	
FRONT	
TAILGATE	
FLOOR	100
SILLS	
SILLS (13' 6"+)	196
BODY WEIGHT	
STANDARD BODY LENGTHS	
STANDARD SIDE HEIGHTS	
STANDARD TAILGATE HEIGHTS	TI S
STANDARD INSIDE WIDTH	
STANDARD HOIST SYSTEM	
OPTIONAL HOIST SYSTEM	

	CSS   Clean side body standard & commercial market	CSM Domex clean side body Municipal & commercial market
	Open "C" fold to the inside	Open "C" fold to the inside
s	3/16" – 44-W	3/16" – Domex 100W
s	NONE	NONE
I	3/16" – 44-W	3/16" - Domex 100W
	3/16" – 44-W	3/16" - Domex 100W
	3/16" – 44-W	1/4" – AR225
s	3/16" – 44-W	3/16" - Domex 100W
)	0.2242" - 44-W	3/16" - Domex 100W
I	2,810 lbs Based on a 10' x 30" x 36" CSS	3,014 lbs Based on a 10' x 30" x 36" CSM
s	9' to 16'	9' to 16'
s	24", 30", 36", 42"	24", 30", 36", 42"
s	30", 36", 42", 48"	30", 36", 42", 48"
H	86" to 88" trapezoidal design	86" to 88" trapezoidal design
M.	Front Mount Telescopic	Front Mount Telescopic
И	Under Body Hoist	Under Body Hoist

# TRADITIONAL BODY LINE



IF OUD ITS SHOWN WAY TIME DEALER INSTALECT	EU UF HUNS. SEE BAUK-FAGE FUR UETAILS	
HS Light duty dump body for single axle trucks	HT   Medium duty dump body for tandem, lift axle trucks	HT-NE Heavy duty dump body for tandem, lift axle trucks
3" x 4" x 3/16" tubing	3" x 4" x 3/16" tubing	3" x 4" x 3/16" tubing
3/16" - 44-W	3/16" - 44-W	3/16" - 44-W
10g (0.134") – A-36	10g (0.134") – A-36	10g (0.134") – A-36
3/16" - 44-W	3/16" - 44-W	3/16" - 44-W
1/4" - 44-W	1/4" - AR225	4.5 mm (3/16") – HARDOX 450
1/4" - AR225	1/4" - AR225	4.5 mm (3/16") – HARDOX 450
3/16" - 44-W	0.2242" - 44W	0.2242" - 44-W
0.2242" - 44-W (13' 6"+)	1/4" - 44W (16' 6"+)	1/4" - 44-W (16' 6"+)
3,220 lbs Based on a 10' x 30" x 36" HS	5,834 lbs Based on a 17" x 48" x 60" HT	5,316 lbs Based on a 17' x 48" x 60" HT-NE
9' to 16'	13' to 18'	13' to 18'
24" to 36"	36" to 54"	36" to 54"
30" to 48"	36" to 60"	36" to 60"
86" to 88" trapezoidal design	86" to 88" trapezoidal design	86" to 88" trapezoidal design
Front Mount Telescopic	Front Mount Telescopic	Front Mount Telescopic
Control of the Contro		

**Under Body Hoist** 

**Under Body Hoist** 

MATERIALS

SPECIFICATIONS

**Under Body Hoist** 

TOP RAIL
SIDES
SIDE POSTS
FRONT
TAILGATE
FLOOR
SILLS
SILLS +
BODY WEIGHT

STANDARD SIDE HEIGHTS
STANDARD TAILGATE HEIGHTS
STANDARD INSIDE WIDTH
STANDARD HOIST SYSTEM
OPTIONAL HOIST SYSTEM

STANDARD BODY LENGTHS

# TRADITION

Front Mount Telescopic

**Under Body Hoist** 

MATERIALS

SPECIFICATIONS



· 美工业	THE	BODIES SHOWN MAY HAVE DEALER INSTALLED OPTIONS. SEE B
	The industry standard for weight sensitive versatile work	HTT   The industry standard for the roughest work
TOP RAIL	3" x 4" x 3/16" tubing	3" x 4" x 3/16" tubing
SIDES	1/8" – AR450	4.5 mm (3/16") – HARDOX 450
SIDE POSTS	10g (0.134") – A-36	10g (0.134") – A-36
FRONT	1/8" – AR450	4.5 mm (3/16") – HARDOX 450
TAILGATE	4.5 mm (3/16") – HARDOX 450	1/4" - HARDOX 450
FLOOR	4.5 mm (3/16") – HARDOX 450	1/4" - HARDOX 450
SILLS	1/4" – 44-W	1/4" — 44-W
SILLS +	8" or 10" I-Beams – (Optional)	8" or 10" I-Beams - (Optional)
BODY WEIGHT	4,796 lbs Based on a 17' x 48" x 60" LTT	5,867 lbs Based on a 17' x 48" x 60" HTT
STANDARD BODY LENGTHS	10' to 23'	10' to 23'
STANDARD SIDE HEIGHTS	36" to 72"	36" to 72"
STANDARD TAILGATE HEIGHTS	36" to 72"	36" to 72"
STANDARD INSIDE WIDTH	86" to 88" trapezoidal design	86" to 88" trapezoidal design

STANDARD HOIST SYSTEM

**OPTIONAL HOIST SYSTEM** 

Front Mount Telescopic

**Under Body Hoist** 

## MULTI-PURPOSE BODY LINE



MPLD   Multi-purpose light duty municipality & landscaping	MPMD   Multi-purpose medium duty landscaping	MPHD   Ideal body for heavy duty clean up and tree service
3" x 4" x 3/16" tubing	3" x 4" x 3/16" tubing	4" x 4" x 1/4" tubing
10g (0.134") – A-36	3/16" - Domex 100W	4.5 mm (3/16") – HARDOX 450
NONE	NONE	NONE
10g (0.134") – A-36	3/16" – Domex 100W	4.5 mm (3/16") – HARDOX 450
12g (0.1046") – A-36	11g (0.1196") – Domex 100W	4 mm (5/32") – HARDOX 450
3/16" - 44-W	3/16" - Domex 100W	1/4" - HARDOX 450
8" C-channel with support flange	8" C-channel with support flange	8" I-beam with support flange
2,845 lbs Based on a 12' x 48" x 16"	3,500 lbs Based on a 15' x 48" x 32"	8,950 lbs Based on a 23' x 60" x 96" x 96"
12' to 18'	12' to 18'	15' to 30'
48", 54" & 60"	48", 54" & 60"	60", 66", 72", 84" & 96"
32", 48", 54" & 60"	32", 48", 54" & 60"	60", 66", 72", 84" & 96"
Same as side height	Same as side height	48" & 60"
87"	87"	86" to 88" trapezoidal design

Front mount telescopic

MATERIALS

SPECIFICATIONS

**Underbody Hoist** 

TOP RAIL
SIDES
SIDE POSTS
FRONT
TAILGATE
FLOOR
SILLS
BODY WEIGHT

STANDARD SIDE HEIGHTS
STANDARD TAILGATE HEIGHTS
STANDARD FRONT HEIGHT
STANDARD INSIDE WIDTH
STANDARD HOIST SYSTEM

STANDARD BODY LENGTHS

**Underbody Hoist** 

# SINGLE, TANDEM AXLE BODY LINE



		THE BODIES SHOWN MAY HAVE DEALE
	DCS   Light-weight clean side body	DLS   Municipal & contractor light-weight body
	Open "C" fold to the inside 48" side – 3" x 4" x 3/16" tubing	3" x 4" x 3/16" tubing
	1/8" – AR450	1/8" - AR450
	NONE	NONE
in a	1/8" – AR450	1/8" - AR450
	4.5 mm (3/16") – HARDOX 450	4 mm (5/32") – HARDOX 450
	4.5 mm (3/16") – HARDOX 450	4 mm (5/32") – HARDOX 450
	3/16" - 44-W	3/16" - 44-W
	0.2242" - 44-W	0.2242" - 44-W
	2,536 lbs Based on a 10' x 30" x 36" DCS	2,540 lbs Based on a 10' x 30" x 36" DLS
	9' to 16'	9' to 16'
	24", 30", 36", 42"*, 48"* (*: two fold side design)	24", 30", 36"
7	30", 36", 42", 48", 54", 60"	30", 36", 42", 48"

86" to 88" trapezoidal design

Front Mount Telescopic

**Under Body Hoist** 

**TOP RAIL** 

SIDES

FRONT TAILGATE **FLOOR** SILLS

SIDE POSTS

SILLS (13' 6"+) **BODY WEIGHT** 

STANDARD BODY LENGTHS

STANDARD SIDE HEIGHTS

STANDARD INSIDE WIDTH

STANDARD HOIST SYSTEM

**OPTIONAL HOIST SYSTEM** 

STANDARD TAILGATE HEIGHTS

3" x 4" x 3/16" tubing	3" x 4" x 3/16" tubing
1/8" – AR450	4 mm (5/32") – HARDOX 450
NONE	NONE
1/8" - AR450	4 mm (5/32") – HARDOX 450
4 mm (5/32") – HARDOX 450	4.5 mm (3/16") – HARDOX 450
4 mm (5/32") – HARDOX 450	4.5 mm (3/16") – HARDOX 450
3/16" - 44-W	3/16" - 44-W
0.2242" - 44-W	0.2242" - 44-W
2,540 lbs Based on a 10' x 30" x 36" DLS	2,697 lbs Based on a 10' x 30" x 36" DHS
9' to 16'	9' to 16'
24", 30", 36"	24", 30", 36"
30", 36", 42", 48"	30", 36", 42", 48"
86" to 88" trapezoidal design	86" to 88" trapezoidal design
Front Mount Telescopic	Front Mount Telescopic
Under Body Hoist	Under Body Hoist

Municipal & contractor heavy duty body

MATERIALS

SPECIFICATIONS

# DIAMOND TANDEM, MULTI-LIFT AXLE BODY LINE



DL	The ultimate solution for weight sensitive versatile work	
3" x 4	1" x 3/16" tubing	

4 mm (5/32") - HARDOX 450

NONE

	3" x 4" x 3/16" tubing
Ý	4.5 mm (3/16") – HARDOX 450
	NONE
	4.5 mm (3/16") – HARDOX 450

4 mm (5/32") – HARDOX 450	
4.5 mm (3/16") – HARDOX 450	
4.5 mm (3/16") - HARDOX 450	
3/16" - Domex 100W	

1/4" - HARDOX 450	
1/4" - HARDOX 450	

4,378 lbs Based on a 17' x 48" x 60"	DL
13' to 24'	9

4,989 lbs	
Based on a 17'	x 48" x 60" DH
A STATE OF THE PARTY OF THE PAR	A TOTAL PROPERTY AND ADDRESS OF THE PARTY AND

13' to 24'

3/16" - Domex 100W

42", 48", 54", 60", 66", 70"
42", 48", 54", 60", 66", 72"
86" to 88" trapezoidal design
Front Mount Telescopic

**Under Body Hoist** 

42", 48", 54", 60", 66", 70"
42", 48", 54", 60", 66", 72"
86" to 88" trapezoidal design
Front Mount Telescopic

**Under Body Hoist** 

SIDES
SIDE POSTS
FRONT
TAILGATE

**TOP RAIL** 

FLOOR SILLS

BODY WEIGHT

STANDARD SIDE HEIGHTS
STANDARD TAILGATE HEIGHTS
STANDARD INSIDE WIDTH
STANDARD HOIST SYSTEM
OPTIONAL HOIST SYSTEM

STANDARD BODY LENGTHS

SPECIFICATIONS

MATERIALS



	П
	ı
TOP RAIL	ı
SIDES	l
SIDE POSTS	
FRONT	ŀ
TAILGATE	ı
	ŀ
FLOOR	ı
SILLS	L
BODY WEIGHT	ı
STANDARD BODY LENGTHS	ľ
STANDARD SIDE HEIGHTS	ı
ANDARD TAILGATE HEIGHTS	
STANDARD INSIDE WIDTH	
STANDARD HOIST SYSTEM	

OPTIONAL HOIST SYSTEM

STANDAR

Marie Carlotte Carlot	BUDIES SHOWN MAT HAVE DEALER INSTALLED OFFICIAS, SEE BACK-PAGE FOR DE	
DBL An ideal body for excavation & light demolition work	DBH   Ideal for heavy duty quarry & demolition work	
4" x 6" x 3/16" tubing	4" x 6" x 1/4" tubing	
4.5 mm (3/16") – HARDOX 450	1/4" – HARDOX 450	
NONE	NONE	
4.5 mm (3/16") – HARDOX 450	1/4" – HARDOX 450	
4.5 mm (3/16") – HARDOX 450	1/4" — HARDOX 450	
4.5 mm (3/16") – HARDOX 450	1/4" — HARDOX 450	
1/4" – 44-W	1/4" — 44-W	
4,948 lbs Based on a 17'6" x 54" x 60" DBL	5,744 lbs Based on a 17'6" x 54" x 60" DBH	
13' to 22'	13' to 22'	
42" to 66"	42" to 66"	
42" to 72"	42" to 72"	
88"	88"	
Front Mount Telescopic	Front Mount Telescopic	
Under Body Hoist	Under Body Hoist	



THE BODIES SHOWN I	BAY WAVE DEALED	MCTALL CH OPTION	STORE BACK D	ICC END NETABLE
THE BULLES SHOWING	WAT MAYE DEVICED	INSTACLED OF HUNG	A SECIDAUNIA	VOICE LEGIT DESIGNICS

	One Ton   Premier light-weight drop side body	Contractor   Premier light-weight double drop side body
	11g (1/8") – Domex 100W	11g (1/8") – Domex 100W
	11g (1/8") – Domex 100W	11g (1/8") – Domex 100W
	11g (1/8") – Domex 100W	11g (1/8") – Domex 100W
	11g (1/8") – Domex 100W	11g (1/8") – Domex 100W
	4.5 mm (3/16") – HARDOX 450	1/4" – HARDOX 450
	8" C-Channel	10" C-Channel with support flange
	*Optional C5" over C4"	NONE
	1,961 lbs Based on a 11' x 15" x 24" One ton (with sub-frame)	3,053 lbs  Based on a 14' x 15" x 24" Contractor (double drop sides)
	8' 6" to 12' 6"	13' to 18'
	12", 15", 18"	12", 15", 18", 20"
	20", 24", 28"	20", 24", 28"
	88"	88"
	Front Mount Telescopic (6" recess)	Front Mount Telescopic (12" recess)
-	Under Body Hoist	Under Body Hoist

**SIDES** 

SIDE POSTS

FRONT

TAILGATE

**FLOOR** 

SILLS

SUB-FRAME

**BODY WEIGHT** 

STANDARD BODY LENGTHS

STANDARD SIDE HEIGHTS

STANDARD TAILGATE HEIGHTS

STANDARD INSIDE WIDTH

STANDARD HOIST SYSTEM

OPTIONAL HOIST SYSTEM

MATERIALS

SPECIFICATIONS

# STAINLESS STEEL MUNICIPAL SS304 BODY LINE

THE BOOKS SHOWN MAY HAVE DEALER INSTALLED DYTICKS. SEE BACK-PACE FURTURIALS

SSM4 A new quality \$\$304 design for the municipal market	BODY OPTIONS
7g (3/16") - SS304 2B (one piece with dirt shedding top rail)	10g (1/8") — SS304 2B (one piece with dirt shedding top rail)
7g (3/16") – SS304 2B	10g (1/8") - SS304 2B
NONE	10g (1/8") - SS304 2B - (Optional)
7g (3/16") – SS304 2B	10g (1/8") – SS304 2B
7g (3/16") – SS304 2B	NONE
4.5 mm (3/16") – HARDOX	7g (3/16") - SS304 2B / 1/4" - HAR
3/16" Domex 100W	7g (3/16") - SS304 2B
2877 lbs	The state of the s

STANDARD HOIST SYSTEM

**TOP RAIL** 

SIDES

FRONT TAILGATE FLOOR

SILLS

Based on a 10' x 30" x 36" SSM4

Front mount telescopic

**BODY WEIGHT** 

SIDE POSTS

**Under Body Hoist** 

- HARDOX 450

# BODY OPTIONS

			4																		TO STORE		
								5	Contractor									-					
	<b>S10</b>	E	55	=	=	B	曹	One-Ton		CSS	CSM	2	=	H	E	E	E E	MPM	E	SSM4			
SIDE DOOR												(2)					•	•					
DOUBLE BARN DOOR			BILL	100	1															9,8			
UPPER SPLIT MESH BARN DOOR																	•	•					
COAL DOORS	•			•		<b>♦</b>	<b>\$</b>			*		•	•			•				•			
DOUBLE-ACTING TAILGATE	•	•	•		•	•	•		•	•	•	•								•			
ASPHALT TAIL							•			•	•	•		•	•	•	Lang.						
SIDE OPENING TAILGATE	•	•	•	•	*	•	•			•	•	•	•						•				
AIR/HYDRAULIC HIGH-LIFT TAILGATES				•	•	•	•						•	•	•	•							
AUTOMATIC TAILGATE					•	•	•						•	•	•	•							
REMOVABLE TOP																	•	•					
CLOSED-OFF TOP RAIL			•							•	•												
10" SILLS		•	•					•	•	•	•	•	•	•			•	•		•			
NON-DUMPING CONTAINER																							
HOOK-LIFT / ROLL-OFF	•	•	•	•	•	727			•	•	•	•	•	•	•	•	•	•					
TAPERED SIDES					•	•	•					•	•	•	•	•							
DROP SIDES								•	•								1						
SUB-FRAME PACKAGE								•	•														
TARP RAILS		•	•	•	•				No. of		•	•		•	•		•		•	1			
UNDER BODY HOIST SYSTEM		•		•	•	•	•	•	•				•	•		•							
	116	141				5/4	171		P. W.	1 7	A 15	1	100	19 75	al	3/3	Min	398	1	84	T. S.		



One centered coal door only

300 Universelle street Vars, Ontario, Canada KOA 3H0 Tel: 613.443.0044 - Fax: 613.443.1138



"Everything for the Trucker" www.truckequipinc.com

### GREEN BAY, WI

Please contact your local dealer, or www.beauroc.com for more information.

680 Potts Ave. Green Bay, WI 54304 (920) 494-7451 (800) 242-7337

### WAUSAU, WI

7202 Zinser Street Schofield, WI 54476 (715) 355-0701 (877) 355-2924

### APPLETON, WI

1750 Prospect Ct. Appleton, WI 54911 (920) 749-4985 (866) 295-4386

### ESCANABA, MI

1919 7th Ave. North Escanaba, WI 49829 (906) 786-2286 (800) 242-3550