

STAHL®

2000F-5-E Manual Rotation  
2000FR-5-E Power Rotation  
Crane Rating: 6,600 ft. lbs.  
Maximum lifting capacity: 2,000 lbs.  
Boom Length: 5' (8' & 10' optional)



### 5-FOOT BOOM REACH

Manual extension boom provides 5-ft. of reach (8-ft. and 10-ft. manual extension optional)

### COMPACT AND VERSATILE

Compact design allows mounting in service bodies, on flatbeds and in pickup beds. Floor-mount and compartment-mount models are available

### OPERATOR-FRIENDLY CONTROLS

Lightweight, multi-function remote control allows for single-handed operation of the crane

### SECURE FROM UNAUTHORIZED USE

Remote control unit can be quickly detached and locked away to prevent unauthorized use of the unit

Floor-mount model pictured

Covered by a  
1-Year Limited Warranty



Get the complete Crane and Crane Body package you need from STAHL

# LIFTING CAPACITIES\* - 2000 SERIES

REACH	RETRACTED BOOM	MANUAL EXTENSION
3 ft.	2,000 lbs.	
4 ft.		1,650 lbs.
5 ft.		1,320 lbs.

\*Double Line is required for 1,000+ lb. loads

## SPECIFICATIONS

DESCRIPTION	2000F-5-E	2000FR-5-E
Boom Rotation	Manual	Power
Total Boom Extension (Max.)	5 ft.	5 ft.
Rotation System	360° continuous manual on turntable bearing	360° continuous electric on turntable bearing with worm drive and dynamic brake
Remote Control	Lightweight removable remote control unit with 10' of cable	Lightweight removable remote control unit with 25' of cable
Winch Cable	50' of 3/16" aircraft cable with latch hook, traveling block and down-haul weight	50' of 3/16" aircraft cable with latch hook, traveling block and down-haul weight
Winch	12V - DC electric	12V - DC electric
Winch Line Speed (no load)	18.5 ft. per minute (single line)	18.5 ft. per minute (single line)
Winch Line Speed (1,000 lbs.)	12.7 ft. per minute (single line)	12.7 ft. per minute (single line)
Winch Line Speed (2,000 lbs.)	3.6 ft. per minute (double line)	3.6 ft. per minute (double line)
Rotation Speed	N/A	1 RPM
Weight	240 lbs.	260 lbs.
Storage Height Folded	51.5 in.	53 in.
Base Dimensions	12 in. x 12 in.	12 in. x 12 in.
Minimum Chassis Requirements	8,000 GVW	8,000 GVW
Power Service Requirements	12V - DC	12V - DC

## OPTIONAL EQUIPMENT:

8 ft. manual extension boom  
10 ft. manual extension boom

### Contact Us

3201 West Old Lincoln Way • Wooster, OH 44691  
Phone: (800) 277-8245  
Fax: (330) 264-0300  
E-mail: [info@stahltruckbodies.com](mailto:info@stahltruckbodies.com)  
Web: [www.stahltruckbodies.com](http://www.stahltruckbodies.com)



STAHL<sup>®</sup>

3200LRX-15-EH

Crane Rating: 12,000 ft. lbs.

Maximum lifting capacity: 3,200 lbs.

Boom Length: 15'



### 15-FOOT TOTAL REACH

Hydraulic extension boom provides 11-ft. of reach with the manual boom adding an 4-ft. of reach

### SMOOTH OPERATION

Self-lubricating Nylatron™ bearing allows for smooth operation of inner and outer booms

### OPERATOR-FRIENDLY CONTROLS

Lightweight, multi-function remote control allows for single-handed operation of the crane

### SECURE FROM UNAUTHORIZED USE

Remote control unit can be quickly detached and locked away to prevent unauthorized use of the unit

Covered by a  
1-Year Limited Warranty



Get the complete  
Crane and Service Body package  
you need from STAHL

# LIFTING CAPACITIES\* - 3200 SERIES

REACH	RETRACTED BOOM	HYDRAULIC EXTENSION	MANUAL EXTENSION
3 ft.	3,200 lbs.		
4 ft.	3,000 lbs.		
5 ft.	2,400 lbs.		
6 ft.	2,000 lbs.		
7 ft.	1,710 lbs.		
8 ft.		1,500 lbs.	
9 ft.		1,330 lbs.	
10 ft.		1,200 lbs.	
11 ft.		1,090 lbs.	
12 ft.			1,000 lbs.
13 ft.			920 lbs.
14 ft.			855 lbs.
15 ft.			800 lbs.

\*Double Line is required for 1,600+ lb. loads

## SPECIFICATIONS

DESCRIPTION	SPECIFICATION
Total Boom Extension (Max.)	15 ft.
Hydraulic Extension	11 ft.
Manual Extension	4 ft.
Rotation System	360° continuous hydraulic on turntable bearing with worm drive and dynamic brake
Remote Control	Lightweight removable remote control unit with 25 ft. of cable
Winch Cable	62 ft. of 1/4" aircraft cable with latch hook, traveling block and down-haul weight
Winch	12V - DC electric motor - 1.8 hp. planetary gear with brake
Winch Line Speed	15 ft. per minute (single line)
Rotation Speed	1 RPM
Boom Elevation	-5° to +75°
Maximum Line Pull	1,600 lbs. single line / 3,200 lbs. double line
Weight	800 lbs.
Length	8 ft. - 11 in.
Width	20 in.
Height	28 in.
Minimum Chassis Requirements	10,000 GVW
Power Service Requirements	12V - DC chassis must have min. 60 amp alternator. Chassis battery must be HD maintenance type with min. 100 minute reserve and 500 cold cranking amps
Outrigger	Truck must be equipped with jackleg or outrigger


### Contact Us

3201 West Old Lincoln Way • Wooster, OH 44691  
 Phone: (800) 277-8245  
 Fax: (330) 264-0300  
 E-mail: info@stahl.cc  
 Web: www.stahltruckbodies.com



4000LRX-16-EH  
Crane Rating: 16,000 ft. lbs.  
Maximum lifting capacity: 4,000 lbs.  
Boom Length: 16 ft.

STAHL®



### 16-FOOT TOTAL REACH

Boom extends hydraulically to 12 ft., the manual slide-out boom extension adds an additional 4 ft.

### SMOOTH OPERATION

Self-lubricating Nylatron™ bearing allows for smooth operation of inner and outer booms

### OPERATOR-FRIENDLY CONTROLS

Lightweight, multi-function remote control allows for single-handed operation of the crane

### SECURE FROM UNAUTHORIZED USE

Remote control unit can be quickly detached and locked away to prevent unauthorized use of the unit

Covered by a  
1-Year Limited Warranty



Get the complete  
Crane and Crane Body package  
you need from STAHL

# LIFTING CAPACITIES - 4000 SERIES

REACH	RETRACTED BOOM	HYDRAULIC EXTENSION	MANUAL EXTENSION
3 ft.	4,000 lbs.		
4 ft.	4,000 lbs.		
5 ft.	3,200 lbs.		
6 ft.	2,660 lbs.		
7 ft.	2,285 lbs.		
8 ft.	2,000 lbs.		
9 ft.		1,775 lbs.	
10 ft.		1,600 lbs.	
11 ft.		1,450 lbs.	
12 ft.		1,330 lbs.	
13 ft.			1,230 lbs.
14 ft.			1,140 lbs.
15 ft.			1,065 lbs.
16 ft.			1,000 lbs.

\*Double Line is required for 2,000+ lb. loads

## DIMENSIONAL SPECIFICATIONS

DESCRIPTION	SPECIFICATION
Base Boom Length	8 ft.
Hydraulic Extension Length	4 ft.
Manual Extension length	4 ft.
Rotation System	360° continuous hydraulic on turntable bearing with worm drive and dynamic brake
Remote Control	Lightweight removable remote control unit with 25 ft. of cable
Winch Cable	100 ft. of 1/4" aircraft cable with latch hook, traveling block and down-haul weight
Winch	12V - DC electric motor - 1.8 hp. planetary gear with brake
Winch Line Speed	15 ft. per minute (single line)
Rotation Speed	1 RPM
Boom Elevation	-5° to +75°
Maximum Single Line Pull	2,000 lbs.
Maximum Double Line Pull	4,000 lbs.
Weight	905 lbs.
Length	9 ft. -7in.
Width	20 in.
Height	28 in.
Minimum Chassis Requirements	10,500 GVW
Power Service Requirements	12V - DC chassis must have min. 60 amp alternator. Chassis battery must be HD maintenance type with min. 100 minute reserve and 500 cold cranking amps
Outrigger	Truck must be equipped with jackleg or outrigger

### Contact Us


3201 West Old Lincoln Way • Wooster, OH 44691

Phone: (800) 277-8245

Fax: (330) 264-0300

E-mail: info@stahl.cc

Web: www.stahltruckbodies.com



STAHL<sup>®</sup>



5000LRX-20-H

Crane Rating: 25,000 ft. lbs.

Maximum lifting capacity: 5,000 lbs.

Boom Length: 20 ft.

### 20-FOOT TOTAL BOOM REACH

Fully hydraulic extension boom provides 20-ft. of reach

### OPERATOR-FRIENDLY WIRELESS REMOTE CONTROLS

Lightweight, proportional wireless FM radio remote control permits single-handed precision operation of the crane

### SMOOTH OPERATION

Self-lubricating Nylatron™ bearing allows for smooth operation of inner and outer booms

### SECURE FROM UNAUTHORIZED USE

Remote control unit can be quickly detached and locked away to prevent unauthorized use of the unit

Covered by a  
1-Year Limited Warranty



Get the complete Crane and Crane Body package you need from STAHL

# LIFTING CAPACITIES\* - 5000 SERIES

REACH	RETRACTED BOOM	FIRST HYDRAULIC EXTENSION	SECOND HYDRAULIC EXTENSION
3 - 5 ft.	5,000 lbs.		
6 ft.	4,160 lbs.		
7 ft.	3,570 lbs.		
8 ft.	3,125 lbs.		
9 ft.	2,775 lbs.		
10 ft.	2,500 lbs.		
11 ft.		2,270 lbs.	
12 ft.		2,080 lbs.	
13 ft.		1,920 lbs.	
14 ft.		1,785 lbs.	
15 ft.		1,665 lbs.	
16 ft.			1,560 lbs.
17 ft.			1,480 lbs.
18 ft.			1,385 lbs.
19 ft.			1,315 lbs.
20 ft.			1,250 lbs.

\*Double Line is required for 2,500+ lb. loads

## SPECIFICATIONS

DESCRIPTION	SPECIFICATION
Base Boom Length	10 ft.
First Hydraulic Extension	5 ft.
Second Hydraulic Extension	5 ft.
Rotation System	370° non-continuous hydraulic on turntable bearing with worm drive and dynamic brake
Remote Control	Lightweight, hand-held, proportional wireless FM radio remote control unit
Winch Cable	100 ft. of 5/16" aircraft cable with latch hook, traveling block and down-haul weight
Winch	Hydraulic planetary gear with brake
Winch Line Speed	60 ft. per minute (single line)
Rotation Speed	1 RPM
Boom Elevation	-5° to +75°
Maximum Line Pull	3,000 lb. single line / 5,000 lb. double line
Weight	950 lbs. (approx.)
Length	11 ft. - 6 in.
Width	20 in.
Height	30 in.
Minimum Chassis Requirements	14,500 GVW
Hydraulic Requirements	Pump output of 8 GPM @ 2750 PSI
Outrigger	Truck must be equipped with heavy-duty outrigger

### Contact Us

3201 West Old Lincoln Way • Wooster, OH 44691

Phone: (800) 277-8245

Fax: (330) 264-0300

E-mail: [info@stahltruckbodies.com](mailto:info@stahltruckbodies.com)

Web: [www.stahltruckbodies.com](http://www.stahltruckbodies.com)

