# GARAGE HEIGHT UTILITY SERVICE VAN

# **UTILITY SERVICE VAN**

The STAHL Garage Height Utility Service Van provides a large enclosed load space area while still providing adequate access clearance for most garages. The sleek body exterior with full- height compartment doors enhance company image while giving maximum access to all your equipment. Each compartment and the loadspace can be configured with optional drawers, racks, trays etc. to fit your specific application needs. Constructed of heavy gauge, powder coated Galvanneal steel, this USV includes fully concealed bolt-on compartment door hinges and L.E.D. lights making it a great value for your fleet!

### MAXIMUM STORAGE - PLENTY OF CLEARANCE

Over 350 sq. ft. of enclosed storage and an overall mounted roof height of less than 90" (excluding ladder rack) which allows adequate clearance for most garages.

### HIGH SECURITY / LOW MAINTENANCE

Hidden door hinges provide security while their bolt-on design makes them maintenance-friendly



#### PROTECTION FOR YOUR VALUABLES

Keyed-alike locks on each compartment door keep valuables secure. Optional, push-pull bar locks with padlock tabs can also be added to provide a second level of security

#### LONG LASTING GOOD LOOKS

The service body exterior, compartment interiors and cargo area surfaces are finished in durable, corrosion-resistant white powder coat

Covered by a 5-Year "No Rust, No Bust" warranty







Large interior load space provides plenty of secured storage

# STANDARD COMPARTMENT CONFIGURATION

COMPARTMENT	CURB-SIDE CONFIGURATION	STREET-SIDE CONFIGURATION		
Front vertical	(2) adjustable tray with moveable dividers	(2) adjustable tray with moveable dividers		
Second vertical	(2) adjustable tray with moveable dividers	(2) adjustable tray with moveable dividers		
Horizontal	(1) adjustable tray with moveable dividers	Open		
Rear vertical	(1) adjustable tray with moveable dividers	(1) adjustable tray with moveable dividers		

# DIMENSIONAL SPECIFICATIONS

DESCRIPTION	DIMENSION		
Overall body length (less bumper)	129"		
Overall body height	66.5"		
Overall body width	84"		
Cab-to-axle	80"		
Rear door opening height	53"		
Loadspace interior height	56.5"		
Loadspace floor width	54"		
Front vertical width / Clear door opening	33.34" / 28.88"		
Second vertical width / Clear door opening	24" / 19.50"		
Horizontal width / Clear door opening	47.31" / 45.31"		
Rear vertical width / Clear door opening	24.25" / 20.19"		
Vertical compartment height / Clear door opening	39.50" / 36.38"		
Horizontal compartment height / Clear door opening	18" / 14.88"		
Side compartment depth	13.69"		
Floor-to-compartment top height	30.38		



Optional Overhead Ladder Rack



Optional Horizontal Compartment Pass-Thru



Optional Bar Locks



Optional Compartment J-Hooks



Optional Drawer Packages



Optional Generator / Welder

# **AVAILABLE OPTIONS INCLUDE:**

Back-Up Alarm • Conduit Tube • Compartment Lights • Conduit Doors • Dome Lights • Drawer Packages • D-Ring Tie Downs • Fixed Trays • Fixed Trays with Dividers • Flip-Up Side Access Doors • Hooks • Heater • Horizontal Compartment Pass-Thru • Ladder Racks (Overhead and Side-Mount) • Louvres • Power Door Lock Kit w/Remote • Roll-Up Rear Door • Roof Vent • Skylight • Slide-Out Trays • Steps (Fold-Down) • Tire Carrier • Work Light, and more

### Contact Us

3201 West Old Lincoln Way • Wooster, OH 44691

Phone: 800-277-8245 E-mail: info@stahl.cc

Web: www.stahltruckbodies.com

# WALK-IN HEIGHT UTILITY SERVICE VAN

(2)

### **UTILITY SERVICE VAN**

The STAHL Walk-In Height Utility Service Van is truly your workshop on wheels. Its sleek exterior body and full- height compartment doors enhance company image while giving maximum access to all of your tools and equipment . Each body compartment along with the loadspace area can be configured with optional drawers, racks, trays, lights, etc., in order to fit your specific application needs. Constructed of powder coated Galvanneal steel, the USV also comes standard with fully concealed bolt-on compartment door hinges, stainless steel latches and L.E.D. lights making great looking, long-lasting service van ideally suited for your fleet!



### **WORK STANDING UP**

72-inch vertical clearance provides enough interior height for the loadspace to be use as a work shop!

### PROTECTION FOR VALUABLES

Keyed-alike locks on each compartment door keep valuables secure. Optional, push-pull bar locks with padlock tabs can also be added to provide a second level of security

### HIGH SECURITY / LOW MAINTENANCE

Hidden door hinges provide added security while their bolt-on design makes them maintenance-friendly

# ENTER & EXIT THE WORK AREA WITH EASE

A drop-step bumper with grip strut step allows easy access to the interior work area

# LONG LASTING GOOD LOOKS

The service body exterior, compartment interiors and cargo area surfaces are finished in durable, corrosion-resistant white powder coat




Hidden Bolt-On Hinges



Stainless Steel Latches





# STANDARD COMPARTMENT CONFIGURATION

COMPARTMENT	CURB-SIDE CONFIGURATION	STREET-SIDE CONFIGURATION		
Front vertical	(2) adjustable tray with moveable dividers	(2) adjustable tray with moveable dividers		
Second vertical	(2) adjustable tray with moveable dividers	(2) adjustable tray with moveable dividers		
Horizontal	(1) adjustable tray with moveable dividers	<b>O</b> pen		
Rear vertical	(1) adjustable tray with moveable dividers	(1) adjustable tray with moveable dividers		

# DIMENSIONAL SPECIFICATIONS

DESCRIPTION	DIMENSION		
Overall body length (less bumper)	129"		
Overall body height	83"		
Overall body width	84"		
Cab-to-axle	80"		
Rear door opening height	67"		
Loadspace interior height	72"		
Loadspace floor width	54"		
Front vertical width / Clear door opening	33.34" / 28.88"		
Second vertical width / Clear door opening	24" / 19.50"		
Horizontal width / Clear door opening	47.31" / 45.31"		
Rear vertical width / Clear door opening	24.25" / 20.19"		
Vertical compartment height / Clear door opening	39.50" / 36.38"		
Horizontal compartment height / Clear door opening	18" / 14.88"		
Side compartment depth	13.69"		
Floor-to-compartment top height	30.38		



Optional Overhead Ladder Rack



Optional Horizontal Compartment Pass-Thru



Optional Bar Locks



Optional Compartment J-Hooks



Optional Drawer Packages



Optional Generator / Welder

# AVAILABLE OPTIONS INCLUDE:

Back-up Alarm • Conduit Doors • Conduit Tube • Compartment Lights • Drawer Packages • Dome Lights • D-Ring Tie Downs • Fixed Trays • Folding Work table • Generators • Horizontal Compartment Pass-Thru • Heater • J-Hooks • Ladder Racks (Roof-Top and Side Mount) • Louvers • Peg Board • Pull Out Shelf • Push-Pull Bar Locks • Remote Power Lock System • Roll Up Rear Door • Roof Vent • Skylight • Slide-Out Trays • Steps • Tire Carrier • Welders • Windows • Work Lights and more...

#### **Contact Us**

3201 West Old Lincoln Way • Wooster, OH 44691

Phone: 800-277-8245 Fax: (330) 264-0300 E-mail: info@stahl.cc

Web: www.stahltruckbodies.com



# Specifications



#### STANDARD CONSTRUCTION

•	Compartment Bottoms	16 ga galvanneal steel
•	Top/Inside Centers14 on DRW 8	& 16 on SRW galvanneal steel
•	Crossmember	7 ga hot rolled steel
•	Compartment Doors (double panel)	20 ga galvanneal steel
•	Double Rear Doors (double panel)	18 ga outer panel, 20 ga galvanneal steel inner panel
•	End Panels (front and rear)	14 ga galvanneal steel
•	End Panels (front on SRW)	16 ga galvanneal steel
•	Fender Panels (die-stamped)	16 ga galvanneal steel
•	Floor (one-piece seamless)	12 ga treadplate steel
•	Intermediate Panels	16 ga galvanneal steel
•	Longitudinals	10 ga galvanneal steel
•	Roof Sides	18 ga galvanneal steel



129 SRW Garage Height model shown with optional Flip-Up Side Access Doors

- Body sides and roof are constructed using lock-bolt fasteners.

Roof Top ......16 ga galvanneal steel

#### STANDARD FEATURES / EQUIPMENT

- Bar Locks Push-Pull Bar Locks provide additional security for side compartments.
- Bulkhead Two-section bulkhead with windowed sliding door provides access from cab into cargo area. Door is also lockable.
- Bumper Drop-step style with grip-strut step provides easy access into cargo area.
- Construction Lock-bolt to provide unbeatable durability, eliminates rust-causing welding and grinding, and promotes corrosion-free, long-lasting product.
- Cutout Opening in intermediate panel between horizontal and rear vertical compartments provides extended storage between compartments.
- Door Frame Reinforced with 7 gauge hot rolled steel
- **Door Hinges –** Concealed, bolt-on style provide increased security and clean appearance. Vertical compartment doors have spring-loaded door holders to hold doors in the open position. Rear doors feature stainless steel strap hinges.
- Door Latches Bolt-on rotary style with stainless steel paddle handles and stainless steel pans.
- Lock Cylinders are keyed alike with double-bitted keys and are power door lock ready for easy after-market installation.
- Door Striker Adjustable, bolt-on.
- **Door Seal –** STAHL-engineered clip-on to allow easy removal for painting, replacement and quicker installation. Door seals against a flat surface for extra protection against water leakage.
- Horizontal Doors Have 2 vinyl coated aircraft cables that support the door while in the open position.
- Drip Rail Concealed to provide extra protection against water leakage.
- Fender Panels Bolt-on die-stamped with radius wheel opening.
- LED Body Lights 6" Oval stop/turn/tail, 6" oval backup and 2" round marker lights
- Loadspace Light One dome light (with switch on light) centered on interior cargo- area ceiling.
- Rear Doors Double rear doors with security screen covered windows, positive latching L-handle, full-framed door opening, stainless steel strap hinges, gas shocks,
- Shelving (Compartment) 14 ga. bolt-in adjustable material trays with dividers.
- Shelving (Cargo Area) Two built-in, full length shelves in interior cargo area.
- Storage Side compartments and interior cargo area
- Powder Coat Finish USV bodies exterior, compartment interiors, cargo area surfaces and bumper are finished in a durable, corrosion resistant white powder coat.
- Wiring Light kit wiring is run in protective loom and meets FMVSS108.
- Undercoating On bottom of floor and wheel wells.
- Aerodynamic Wind Deflector Standard on Walk-In Height (SRW) models only. Not available on Standard Height or garage Height models
- **STAHL** Exclusive 5-year "No Rust, No Bust" warranty.

Continues on reverse side.

#### STANDARD COMPARTMENTATION

COMPARTMENT	BODY SIZE	CURBSIDE	STREETSIDE
Front Vertical	128"/134"	(2) adjustable material tray with dividers	(2) adjustable material trays with dividers
Second Vertical	128"/134"	(2) adjustable material tray with dividers	(2) adjustable material trays with dividers
Horizontal	128"/134"	(1) adjustable material tray with dividers	Open
Rear Vertical	128"/134"	(1) adjustable material tray with dividers	(1) adjustable material tray with dividers
Front Vertical	157"	(2) adjustable material trays with dividers	(2) adjustable material trays with dividers
Second Vertical	157"	(2) adjustable material tray with dividers	(2) adjustable material trays with dividers
Third Vertical	157"	(2) adjustable material tray with dividers	(2) adjustable material trays with dividers
Horizontal	157"	(1) adjustable material tray with dividers	Open
Rear Vertical	157"	(1) adjustable material tray with dividers	(1) adjustable material tray with dividers

#### **DIMENSIONAL SPECIFICATIONS**

DESCRIPTION	129" SRW GARAGE HEIGHT	129" SRW WALK-IN HEIGHT	134" DRW STD HEIGHT	134" DRW WALK-IN HEIGHT	158" DRW STD HEIGHT	158" DRW WALK-IN HEIGHT
Overall Body Length, less bumper	129"	129"	134"	134"	157"	157"
Overall Body Height	66.5"	83"	75"	83"	75"	83"
Overall Body Width	84"	84"	94.5"	94.5"	94.25"	94.5"
Cab-to-axle	80"	80"	80"	80"	100"	100"
Rear Door Opening Height	53"	67"	60"	67"	60"	67"
Loadspace Interior Height	56.5"	74"	65"	74"	65"	74"
Loadspace Floor Width	54"	54"	64.25"	64.25"	64.25"	64.25"
Front Vertical Width	33.34"	33.34"	33.34"	33.34"	29.75"	29.75"
Clear door opening	28.88"	28.88"	28.88"	28.88"	25.5"	25.5"
Second Vertical Width	24"	24"	24"	24"	26.56"	26.56"
Clear door opening	19.5"	19.5"	19.5"	19.5"	22.3"	22.3"
Third Vertical width	n/a	n/a	n/a	n/a	20"	20"
Clear door opening	n/a	n/a	n/a	n/a	15.75"	15.75"
Horizontal Width	47.3"	47.3"	47.3"	47.3"	47.3"	47.3"
Clear door opening	45.3"	45.3"	45.3"	45.3"	45.7"	45.7"
Rear Vertical Width	24.25"	24.25"	29.75"	29.75"	33.3"	33.3"
Clear door opening	20.25"	20.2"	25.75"	25.75"	29.31	29.31"
Vertical Compartment Height	39.5"	39.5"	39.5"	39.5"	39.5"	39.5"
Clear door opening	36.4"	36.4"	36.4"	36.4"	36.4"	36.4"
Horizontal Compartment Height	18"	18"	18"	18"	18"	18"
Clear door opening	14.88"	14.88"	14.88"	14.88"	14.88"	14.88"
Side Compartment Depth	13.7"	13.7"	13.7"	13.7"	13.7"	13.7"
Floor-to-Compartment Top Height	30.5"	30.5"	30.5"	30.5"	30.5"	30.5"

#### **OPTIONAL EQUIPMENT**

- Back Up Alarm
- Solid Bulkhead
- Bumpers
- Compartment Lights
- Drawers
- Fuel Fill (Alum)
- Flip-Up Side Access Doors
- Folding Steps & Grab Handles
- Hitches
- Hooks
- Horizontal Compartment Pass-Thru Window
- Ladder Rack (roof & side mount) Shelves
- Louvers
- Paint
- Pipe Carriers
- Power Door Locks
- Roll Up Rear Door
- Tie Down Rings
- Tire Carrier
- Trays
- · Windows in sides of roof



Due to constant product evaluations and improvements, specifications and options are subject to change without notice.